

OTAKE

2026

1 machine, 2 steps, with one machine
both rice dehulling and milling

AGRICULTURAL MACHINERY CO.,LTD.

<https://www.otake-ss.co.jp>

PM series

PM500NE / PM1500R

- The paddy input hopper has been lowered to 540 mm. A new paddy bag stand with a height of 300 mm has also been added as part of the standard delivered set, reducing the physical effort required during operation.
- The foreign object remover and brown rice outlet shutter are included as standard delivered parts.

PM500NE

Rice hulling and milling
Simultaneous operation /
Single operation

Husking capacity
100~140kg/h

Milling Capacity
33~38kg/h



- Through a timer, operation time can be set.



PM500NE	
Length, Width, Height (mm)	960×665×1,225
Weight (kg)	85
Motor	1-phase 100V/750W
Hopper volume (kg)	8
Husking Capacity (kg/h)	100~140
Brown rice hopper volume (kg)	18
Rice milling capacity (kg/h)	33~38

PM1500R

Rice hulling and milling
Simultaneous operation

Husking capacity
100~140kg/h

Milling Capacity
100~120kg/h



- Through a timer, operation time can be set.
- The mounting position of the immature rice discharge can be changed to suit the work location.



PM1500R	
Length, Width, Height (mm)	985×675×1,225
Weight (kg)	98
Motor	3-phase 200V/1.5Kw
Hopper volume (kg)	8
Husking Capacity (kg/h)	100~140
Brown rice hopper volume (kg)	6
Rice milling capacity (kg/h)	100~120

HIGH CAPACITY · LIGHT · COMPACT